



 **E-CHRONOS**
radio controls

CATALOG

“ One of the Best
Range in the market of
safety remote control,
feedback included. ”

E-Chronos industrial remote control,
the modern way to control your machine.

Transmitters

Receivers

Accessories

**WHO
ARE
WE?**



CONTROLLING YOU SAFELY

E-Chronos is a Swiss Company developing and producing Radio Remote Controls for industrial application. It's made by a great experience crew with a very long technical and high quality background.

Safety, precision, sturdness, high technology, advanced software configuration and reliability are only few of the features that make this product a true excellence in the telecommunications sector applied to the industry.

E-CHRONOS

We are a team of passionate people whose goal is to ease integrating a safety remote control on your machine.

PROCESS

Switzerland is a very famous country all over the world for the very high quality and precision of its watches production.

E-Chronos name wanted to remember from where we're coming, Cronos was the personification of time in Greek mythology

It's the first time that a crew of high level Swiss engineers are designing something extremely new in the sector of the industrial controls and telecommunication. Thanks to a mix of them together to a big experienced people coming from France, Italy and Germany, was possible to create a work team with a lot of new ideas to improve the Radio Remote Control philosophy.

When we think to Radio Controls producers, we always think to the same companies existing for a long time. Something is slowly but surely changing from now, E-Chronos is another brand new way and idea to say Radio Remote Controls.

OUR TRANSMITTERS



LONG RANGE

Originally intended for forestry applications, our radio link is among the most powerful on the market, including feedback.



ROBUSTNESS / RELIABILITY

Careful selection of the supply chain and our partners in all aspects.




LIGHTWEIGHT / COMPACT

Central point to the development of our models, for the comfort of users. A maximum of functions in a minimum of volume.



CUSTOMIZATION

Easily configurable by the customer, you have access to our software allowing high customization of automation and security.



ERGONOMICS / DESIGN

Our products are internally designed and guided by our customers.

EXPERIENCE

E-Chronos relies on a network of experienced partners in various sectors

Push Vision

PRODUCT

The Push Vision is a transmitter that can control different machines. It is also fully customisable if you want options other than our catalogue models.

COMPATIBILITY

All E-Chronos Push Vision transmitters are compatible with E-Chronos receivers. If physical receiver needed, make sure you have enough output and pins on the receiver.

EQUIPMENT

All E-Chronos Push Vision transmitters are equipped with emergency stop button. Toggles Switchies are ON-OFF-ON. Joysticks are proportionals.

DIMENSION

- **Length** : 181 millimeters.
- **Width** : 102 millimeters.
- **Height** : 65 millimeters.

BATTERY

- **Voltage** : 3,7V lithium
- **Autonomy** : > 30h, > 9h with screen

WEIGHT

- **Weight** : 550g.

MANDATORY ACCESSORIES

- **Additional battery pack**
 - a** Battery Kit (2x battery + charger)
- **Carrying case**
 - b** E-Chornos carrying-case
 - c** Neck Belt



FAST DELIVERY

PUSH VISION A-E-F-Ø-L

PUSH VISION B-D-G-T-L

PUSH VISION C-D-F-T-L

ALL TRANSMITTERS ARE CUSTOMISABLE

ADDING BUTTONS

**CREATION OF
CUSTOM STICKERS**

CASE COLOUR

OPTIONS AVAILABLE ON REQUEST

1 FUNCTION



10 single step button




10 double step button




8 push buttons - 1.8" black and white screen

2 LATERAL BUTTON



With button



Without button

3 STICKER



Numerical sticker



Arrow color sticker

4 START BUTTON




Button



Toggle
1 / 1+2 / 2

5 FREQUENCY



868 mhz




920 mhz

PUSH VISION CODIFICATION / REFERENCE

1	A	B	C
2	D	E	
3	F	G	
4	Ø	T	
5	L	H	

To compose your Push Vision transmitter, select one choice per line. Example: A-F-T-H

CONFIGURE YOUR PUSH VISION TRANSMITTER



Firefly

PRODUCT

The Firefly is a transmitter that can control different machines. It is also fully customisable if you want options other than our catalogue models.

COMPATIBILITY

All E-Chronos Firefly transmitters are compatible with E-Chronos receivers. If physical receiver needed, make sure you have enough output and pins on the receiver.

EQUIPMENT

All E-Chronos Firefly transmitters are equipped with emergency stop button:
- Toggles Switchies are Momentary - OFF - Momentary.
- Joysticks are proportionals.

DIMENSION

- **Length** : 181 millimeters.
- **Width** : 102 millimeters.
- **Height** : 65 millimeters.

BATTERY

- **Voltage** : 3,7V lithium
- **Autonomy** : > 30h

WEIGHT

- **Weight** : 550g.

MANDATORY ACCESSORIES

- **Additional battery pack**
 - a** Battery Kit (2x battery + AC/DC charger)
- **Carrying case**
 - c** Neck Belt



**FAST
DELIVERY**

FIREFLY A-E-T-L

FIREFLY B-E-T-L

**ALL TRANSMITTERS
ARE CUSTOMISABLE**


ADDING BUTTONS

**CREATION OF
CUSTOM STICKERS**


CASE COLOUR

OPTIONS AVAILABLE ON REQUEST

1 FUNCTION



11 toggles switch



7 toggles switch



8 toggles switch - 1 joystick



2 Joysticks + 5 Toggles

FIREFLY CODIFICATION / REFERENCE

1	A	B	C	D
2	E	F		
3	∅	T		
4	L	H		

To compose your Firefly transmitter, select one choice per line. Example: A-E-∅-L

2 STICKER



Numerical sticker



No sticker

3 START BUTTON



Button



Toggle

4 FREQUENCY


L

868 mhz

H

920 mhz

CONFIGURE YOUR FIREFLY TRANSMITTER



M-fly

PRODUCT

The M-fly is a two-handed transmitter that can control different machines. It is also fully customisable if you want options other than our catalogue models.

COMPATIBILITY

All E-Chronos M-Fly transmitters are compatible with E-Chronos receivers.

EQUIPMENT

All E-Chronos M-Fly transmitters are equipped with emergency stop button.

DIMENSION

- **Length** : 215 millimeters.
- **Width** : 141 millimeters.
- **Height** : 143 millimeters.

BATTERY

- **Voltage** : 3.7V lithium
- **Autonomy** : > 30h, > 9h with screen

WEIGHT

- **Weight** : 700g.

MANDATORY ACCESSORIES

- **Additional battery pack**
 - a** Battery Kit (2x battery + charger)
- **Carrying case**
 - c** Neck Belt
 - d** Pictogram sticker sold separately
 - e** Ultra long range, patch antenna



FAST DELIVERY

M-FLY A-D-P-R-L

M-FLY A-F-Q-R-L

M-FLY Cc-E-Q-R-L

ALL TRANSMITTERS ARE CUSTOMISABLE

ADDING BUTTONS

**CREATION OF
CUSTOM STICKERS**

CASE COLOUR

OPTIONS AVAILABLE ON REQUEST

1 MAIN SIDE



4 Joysticks linear



6 Joysticks linear



2 directional Joysticks

a 2x 2 analog joysticks

b 2x 2-2 digital steps

c 1x 3-4 digital steps (left)
1x 1-4 digital steps (right)

M-FLY
CODIFICATION / REFERENCE

1	A	B	Ca	Cb	Cc
2	D	E	F		
3	P	Q			
4	R	S			
5	L	H			

To compose your M-Fly transmitter, select one choice per line. Example: A-D-P-S-H

2 TOP SIDE



1 Start + 2 MOM



1 Start + 1 ON/OFF + 1 MOM



4 pushes + 2.6" color screen + 1 Start (Left)

3 RIGHT SIDE



nothing



2 toggles + 2 pushes

4 LEFT SIDE



nothing



2 toggles + 2 pushes

5 FREQUENCY




868 mhz



920 mhz

CONFIGURE YOUR M-FLY TRANSMITTER



X-fly

PRODUCT

The X-fly is a two-handed transmitter that can control different machines. It is also fully customisable if you want options other than our catalogue models.

COMPATIBILITY

All E-Chronos X-Fly transmitters are compatible with E-Chronos receivers.

EQUIPMENT

All E-Chronos X-Fly transmitters are equipped with emergency stop button.

DIMENSION

- **Length** : 275 millimeters.
- **Width** : 175 millimeters.
- **Height** : 143 millimeters.

BATTERY

- **Voltage** : 3.7V lithium
- **Autonomy** : > 30h, > 9h with screen

WEIGHT

- **Weight** : 750g.

MANDATORY ACCESSORIES

- **Additional battery pack**
 - a** Battery Kit (2x battery + charger)
- **Carrying case**
 - c** Neck Belt
 - d** Pictogram sticker sold separately
 - e** Ultra long range, patch antenna



FAST DELIVERY

X-FLY A-E-P-R-L

X-FLY A-G-Q-R-L

X-FLY D-E-P-R-L

ALL TRANSMITTERS ARE CUSTOMISABLE


ADDING BUTTONS

**CREATION OF
CUSTOM STICKERS**


CASE COLOUR

OPTIONS AVAILABLE ON REQUEST

1 MAIN SIDE



8 linear joystick



6 linear joystick



2x3 axis joystick



3x2 axis joystick

X-FLY
CODIFICATION / REFERENCE

1	A	B	C	D
2	E	F	G	
3	P	Q		
4	R	S		
5	L	H		

To compose your X-Fly transmitter, select one choice per line. Example: A-G-P-S-H

2 TOP SIDE



1 ON-OFF / 3 MOM / 1 push



1 Pot / 3 MOM / 1 Push



1 screen + 6 pushes + 1 Start (Left)

3 RIGHT SIDE



nothing



2 toggles + 2 pushes

4 LEFT SIDE



nothing



2 toggles + 2 pushes

5 FREQUENCY




868 mhz



920 mhz

CONFIGURE YOUR X-FLY TRANSMITTER



OUR RECEIVERS





RXps

PRODUCT

The smallest receiver of E-Chronos RXps can handle CAN and up to 16 physical output. It's the cost effective solution for CAN or limited functions on a application.

COMPATIBILITY

All E-Chronos RXps receivers are compatible with E-Chronos transmitters.

EQUIPMENT

The new born RXps includes a 2x7 digit to ease diagnostic in the fields.



1 CONNECTOR



Amphenol 7 pol



Sicma 24 pol

2 BUTTONS



without button



Manual / OFF / Radio

3 ANTENNA



Internal antenna
(short range, no metal box)



Antenna
(Long range or RXm in metal box + antenna extension)

4 CARDS



CAN (DC)



16 Dig (DC)

5 FREQUENCY



868 mhz



920 mhz

ADAPTABILITY

Based on the motherboard selection, you can :

- **DC card :**
Max current 3A, **1**, **2** up to 8 + 4x2 PWM Hbridge channel output which. 2 digital output can have a different potential.
- **Main contact :** 12A, replaceable protection fuse.
- **canOPEN protocol :** Activated with the dipswitches on the receiver boards.

DIMENSION

- **Length :** 161 millimeters.
- **Width :** 116 millimeters.
- **Height :** 64 millimeters.

USB

USB port to download custom software created with EDrop, USB-C connector.

SECURITY

Safety circuit with two emergency relays, PLe category 3.

ACCESSORY COMPATIBLE WITH TNC CONNECTOR

- **r1** 868-915 MHz long range, $\lambda/2$, 210mm
- **Antenna extension TNC :**
- **u1** 1 m **u3** 3 m **u6** 6 m
- **u10** 10 m **e20** 20 m **u25** 25 m

OPTIONAL ACCESSORIES

- **Choc absorber :**
- **s1** 4x Rubber MM with 2x screws
- **s2** 4x Rubber FF with 2x nuts
- **s3** 4x Rubber MF with 1 screw + 1 nut
- **Connector Kit :**
- **k1** Counter Plug
- **k2** Cable Counter Plug (3 meters)

RXps CODIFICATION / REFERENCE

1	A	B
2	∅	T
3	U	V
4	1	2
5	L	H


To compose your RXps receiver, select one choice per line. Example: B-T-U-2-H

FAST DELIVERY

RXps B-T-U-2-L

RXps B-∅-V-1-L

CONFIGURE YOUR RXPS RECEIVER



RXm

PRODUCT


The RXm with its 2 families of electronic cards (AC and DC) and its 5 different connectors, chosen among the most used, allow a great variety of applications. It is suitable for mobile applications (12-24VDC) or static applications (24-48-230VAC).

COMPATIBILITY

All E-Chronos RXm receivers are compatible with E-Chronos transmitters.

EQUIPMENT


All E-Chronos RXm receivers are equipped with LEDs for immediate diagnosis of operation.



1 CONNECTOR




24 pol



32 pol



AmpSeal 35 Pol



Press Tube
Ø 1-17mm

2 BUTTONS



without button



Manual/Radio
Toggle + EStop

3 ANTENNA



Internal antenna
(short range, no metal box)



Antenna
(Long range or RXm in metal
box + antenna extension)

4 CARDS



19 relays output



23 relays output

DIGITAL PROGRAMMATION



8dig
+ 4 prop



8dig
+ 6 prop



8dig
+ 8 prop

PROPORTIONAL SOFTWARE



PWM-dig



Danfoss




0-10V

5 INTERNAL WIRING



Wired



Not Wired

6 FREQUENCY



868 mhz



920 mhz

ADAPTABILITY

Depending on the selected motherboard you can have up to 24 outputs and 4 inputs.

- **AC card :**
Maximum current 5A : **1** (19 relay outputs) or **2** (23 relay outputs), 4 digital inputs.

- **DC card :**
Maximum current 3A:

- 4** 8dig + 4x2 proportional channels;
- 6** 8dig + 6x2 proportional channels;
- 8** 8dig + 8x2 proportional channels;

which can be transformed into :

- a** PWM-Dig
- b** Danfoss (25%, 50%, 75%)
- c** 0-10V

with different software. Within 4 inputs (dig, 0-30V, 0-20mA).

- **Main contact :** 12A, replaceable protection fuse.

- **canOPEN protocol :** Activated with the dipswitches on the receiver boards.

DIMENSION

- **Length :** 233 millimeters.
- **Width :** 176 millimeters.
- **Height :** 80 millimeters.

USB

USB port to download custom software created with EDrop. USB-C connector.

SECURITY

Safety circuit with two emergency relays, PLe category 3.

ACCESSORY COMPATIBLE WITH TNC CONNECTOR

r1 868-915 MHz long range, $\lambda/2$, 210mm

- **Antenna extension TNC :**

u1 1 m **u3** 3 m **u6** 6 m

u10 10 m **e20** 20 m **u25** 25 m

OPTIONAL ACCESSORIES

- **Choc absorber :**

s1 4x Rubber MM with 2x screws

s2 4x Rubber FF with 2x nuts

s3 4x Rubber MF with 1 screw + 1 nut

- **Connector Kit :**

k1 Counter Plug

k2 Cable Counter Plug (3 meters)

RXm CODIFICATION / REFERENCE

1	A	B	C	D
2	Ø	T		
3	U	V		
4	19	23	4a	4b
	4c	6a	6b	6c
	8a	8b	8c	
5	W	N		
6	L	H		

To compose your RXm receiver, select one choice per line. Example: A-T-U-8c-W-H

FAST DELIVERY


RXm D-Ø-V-23-N-L

RXm C-Ø-V-4a-W-L

RXm C-Ø-V-6a-W-L

RXm C-Ø-V-8a-W-L

CONFIGURE YOUR RXM RECEIVER



RXt

PRODUCT


The RXt can handle 2 RXm product. Motherboard can be connected together to be a bigger receiver and handle up to 48 output and 8 inputs. As the RXm, it can be AC or DC, respectively relay or transistor or be a mix of both types.

COMPATIBILITY

All E-Chronos RXt receivers are compatible with E-Chronos transmitters.

EQUIPMENT


All E-Chronos RXt receivers are equipped with LEDs for immediate diagnosis of operation.



1 CONNECTOR



64 pol



No connector

2 BUTTONS



without button



Manual/Radio Toggle + EStop

3 CARDS



2xMU + 8xPWM (AC)




DIGITAL PROGRAMMATION



2xMU + 8xPWM (DC)



2xMU + 12xPWM (DC)



2xMU + 16xPWM (DC)



1xK19+MU2-8PWM (AC + DC)

PROPORTIONAL SOFTWARE



PWM-dig




Danfoss




0-10V

4 INTERNAL WIRING



Wired



Not Wired

5 FREQUENCY



868 mhz



920 mhz

ADAPTABILITY

Based on the motherboard selection, you can :

- **AC card :**
Maximum current 5A : **1** up to 38 relays outputs and 8 digitales inputs. Up to 8 different potential.
- **DC card :**
Maximum current 3A:
8 16 digit + 8x2 proportional channel;
12 16 digit + 12x2 proportional channel;
16 16 digit + 16x2 proportional channel;

which can be transformed into :

- a** PWM-Dig
- b** Danfoss (25%, 50%, 75%)
- c** 0-10V

- **AC and DC :**
3 19x5A relay output + 8x3A transistor output + 8x2 propotional channel output which mode can be change via software. Up to 5 different potential.
- **Main contact :** 12A, replaceable protection fuse.
- **canOPEN protocol :** Activated with the dipswitches on the receiver boards.

DIMENSION

- **Length :** 255 millimeters.
- **Width :** 250 millimeters.
- **Height :** 123 millimeters.

USB

USB port to download custom software created with EDrop. Micro-USB connector.

SECURITY

Safety circuit with two emergency relays, PLe category 3.

REQUIRED ACCESSORIES

- **Antenna choice :**

r1 868-915 MHz long range, $\lambda/2$, 210mm

OPTIONAL ACCESSORIES

- **Antenna extension TNC :**

u1 1 m **u3** 3 m **u6** 6 m

u10 10 m **u20** 20 m **u25** 25 m

- **Choc absorber :**

s1 4x Rubber MM with 2x screws

s2 4x Rubber FF with 2x nuts

s3 4x Rubber MF with 1 screw + 1 nut

- **Connector Kit :**

k1 Counter Plug

k2 Cable Counter Plug (3 meters)

RXt CODIFICATION / REFERENCE

1	A	B	C	D	
2	Ø	T			
3	1	8a	8b	8c	12a
	12b	12c	16a	16b	16c
	3a	3b	3c		
4	W	N			
5	L	H			


To compose your RXt receiver, select one choice per line. Example: A-T-12c-W-L

FAST DELIVERY

RXt B-Ø-1-N-L

RXt B-Ø-16a-N-L

CONFIGURE YOUR RXt RECEIVER



OUR ACCESSORIES





Transmitter accessories

Additional battery pack



Charger



Adaptaters



2x battery

Carrying case




e-chronos carrying case

Neck Belt



e-chronos neck belt

Pictogram sticker



e-chronos Stickers

Ultra long range



Ultra long range, patch antenna

Receiver accessories

Antenna



868-915 MHz long range, $\lambda/2$, 210mm

Extension TNC :

- | | | | |
|------------|------|------------|------|
| u1 | 1 m | u3 | 3 m |
| u6 | 6 m | u10 | 10 m |
| u20 | 20 m | u25 | 25 m |

Connector Kit




Counter Plug



Cable Counter Plug (3 meters)

Choc absorber



4x Rubber MM with 2x nuts



4x Rubber FF with 2x screws



4x Rubber MF with 1 screw + 1 nut



CONTACT US

E-CHRONOS SA
Rue d'Airmont 5
CH-2900 Porrentruy

 +41 (0) 32 552 0990

 info@e-chronos.ch